

NITROGEN, REFRIGERATED LIQUID Safety Data Sheet

1. IDENTIFICATION

Product identifier

Product Name NITROGEN, REFRIGERATED LIQUID

Other means of identification

Safety data sheet number LIND-P087 UN/ID no. UN1977 Synonyms Nitrogen, liquid

Recommended use of the chemical and restrictions on use

Recommended Use Industrial and professional use.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Linde Gas Singapore Pte Ltd

50 Jurong Island Highway, Singapore 627877

Phone: +65 68678998 www.linde.com.sg

For additional product information contact your local customer service.

Emergency telephone number

Company Phone Number +65 68670860

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

	Refrigerated liquefied gas
Simple asphyxiants	Yes

Label elements



Signal word Warning

Hazard Statements

Contains refrigerated gas; may cause cryogenic burns or injury May displace oxygen and cause rapid suffocation

Precautionary Statements - Prevention
Do not handle until all safety precautions have been read and understood
Use and store only outdoors or in a well ventilated place
Wear cold insulating gloves/face shield/eye protection
Use backflow preventive device in piping
Do NOT change or force fit connections
Close valve after each use and when empty
Always keep container in upright position

Precautionary Statements - Response

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention/advice.

IF ON SKIN:. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Volume %	Chemical Formula
Nitrogen	7727-37-9	100	N 2

4. FIRST AID MEASURES

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If

breathing has stopped, give artificial respiration. Get medical attention immediately.

Skin contact For dermal contact or suspected frostbite, remove contaminated clothing and flush affected areas

with lukewarm water. DO NOT USE HOT WATER. A physican should see the patient promptly if contact with the product has resulted in blistering of the dermal surface or in deep tissue freezing.

Eye contact If frostbite is suspected, flush eyes with cool water for 15 minutes and obtain immediate medical

attention.

Ingestion Not an expected route of exposure.

Self-protection of the first aider RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS.

Most important symptoms and effects, both acute and delayed

Symptoms Simple asphyxiant. May cause suffocation by displacing the oxygen in the air. Exposure to

oxygen-deficient atmosphere (<19.5%) may cause dizziness, drowsiness, nausea, vomiting, excess salivation, diminished mental alertness, loss of consciousness and death. Exposure to atmospheres containing 8-10% or less oxygen will bring about unconsciousness without warning and so quickly that the individuals cannot help or protect themselves. Lack of sufficient oxygen may cause serious

injury or death. Contact with liquid may cause cold burns/frostbite.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific extinguishing methods

Continue to cool fire exposed cylinders until flames are extinguished. Damaged cylinders should be handled only by specialists.

Specific hazards arising from the chemical

Non-flammable gas. Cylinders may rupture under extreme heat.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.

Monitor oxygen level. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use personal protection recommended in Section 8.

Other Information When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely

to break without warning.

Environmental precautions

Environmental precautions Prevent spreading of vapors through sewers, ventilation systems and confined areas.

Methods and material for containment and cleaning up

Methods for containment Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is

in container or container valve, contact the appropriate emergency telephone number in Section 1

or call your closest Linde location.

Methods for cleaning up Return Portable Cryogenic Container to Linde or an authorized distributor.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Never allow any unprotected part of the body to touch uninsulated pipes or vessels that contain cold fluids. The extremely cold metal will cause moist flesh to stick fast and tear when one attempts to withdraw from it. Do NOT change or force fit connections.

Liquid nitrogen is delivered into stationary vacuum jacketed vessels at the customer's location or in portable vacuum-jacketed "liquid" cylinders requiring special handling methods. Consult manufacturer's instructions.

Due to the extremely cold liquid, uninsulated transfer may condense air. The liquefied air may flash off nitrogen, leaving an oxygen enriched liquid. Do not allow the liquefied air to contact oils, grease, or other combustible materials such as asphalt or motor oil. Vessels for liquid nitrogen are designed specifically for nitrogen service. Vessels and associated structures are not designed to support higher density fluids. Density, liquid at saturation pressure at 2.17°K (-271°C): 0.146 Kg/l.

Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distance, use a cart designed to transport cylinders. Never attempt to lift a cylinder by its valve protection cap. Never insert an object (e.g. wrench, screwdriver, pry bar,etc.) into valve cap openings. Doing so may damage valve, causing leak to occur. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Use only with adequate ventilation. Use backflow preventive device in piping. Use an adjustable strap wrench to remove over-tight or rusted caps. Close valve after each use and when empty. Ensure the complete gas system has been checked for leaks before use.

Never put cylinders into trunks of cars or unventilated areas of passenger vehicles. Never attempt to refill a compressed gas cylinder without the owner's written consent. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit.

Only experienced and properly instructed persons should handle gases under pressure. Always store and handle compressed gas cylinders in accordance with Compressed Gas Association, pamphlet CGA-P1, Safe Handling of Compressed Gases in Containers. Use only with equipment rated for cylinder pressure.

For additional recommendations, consult Compressed Gas Association's Pamphlets, AV-8, CGA-341, G-10.1, P-1,P-9,P-12,P-14, and P-18.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Store in cool, dry, well-ventilated area of non-combustible construction away from heavily trafficked areas and emergency exits. Keep at temperatures below 52°C / 125°F. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Use a "first in-first out" inventory system to prevent full cylinders from being stored for excessive periods of time. Full and empty cylinders should be segregrated. Stored containers should be periodically checked for general condition and leakage.

Incompatible materials

None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Appropriate engineering controls

Engineering Controls Ventilation systems. Local exhaust ventilation to prevent accumulation of high concentrations and

maintain air-oxygen levels at or above 19.5%. Oxygen detectors should be used when asphyxiating

gases may be released. Showers. Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear:. Goggles.

Face-shield.

Skin and body protection Work gloves and safety shoes are recommended when handling cylinders. Wear cold insulating

gloves when handling liquid.

Respiratory protection Use positive pressure airline respirator with escape cylinder or self contained breathing apparatus

for oxygen-deficient atmospheres (<19.5%).

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Do not get in eyes, on skin,

or on clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Refrigerated liquefied gas

Appearance Colorless.
Odor Odorless.

Odor threshold No information available pH No data available
Melting point -209.9 °C / -345.9 °F
Evaporation rate Not applicable
Lower flammability limit: Not applicable

Upper flammability limit:

Flash point

Autoignition temperature

Decomposition temperature

Water solubility

Partition coefficient

Kinematic viscosity

Not applicable

Not applicable

No data available

Very slight

No data available

No data available

Not applicable

Che	emical Name	Molecular weight	Boiling point	Vapor Pressure	Vapor density (air	Gas Density	Critical
		_			=1)	Kg/m³@20°C	Temperature
	Nitrogen	28.01	-196 °C	Above critical	0.97	1.153	-146.9 °C
				temperature			

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

None under recommended storage and handling conditions (see Section 7).

Incompatible materials

None known.

Hazardous Decomposition Products

None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Product is a simple asphyxiant.

Skin contact Contact with liquid may cause cold burns/frostbite.

Eye contact Contact with liquid may cause cold burns/frostbite.

Ingestion Not an expected route of exposure.

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

IrritationNot classified.SensitizationNot classified.Germ cell mutagenicityNot classified.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens listed by OSHA, IARC or NTP.

Reproductive toxicity
Developmental Toxicity
Not classified.
STOT - single exposure
STOT - repeated exposure
Chronic toxicity
None known.
Aspiration hazard
Not classified.
Not applicable.

Numerical measures of toxicity

Product Information

Oral LD50 No information available
Dermal LD50 No information available
Inhalation LC50 No information available
Inhalation LC50 No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No known acute aquatic toxicity.

Persistence and degradability

Not applicable.

Bioaccumulation

No information available.

Other adverse effects

Can cause frost damage to vegetation.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Do not attempt to dispose of residual waste or unused quantities. Return in the shipping container

PROPERLY LABELED WITH ANY VALVE OUTLET PLUGS OR CAPS SECURED AND VALVE PROTECTION CAP

IN PLACE to Linde for proper disposal.

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class 2.2

Special Provisions T75, TP5, 346, 345

Description UN1977, Nitrogen, refrigerated liquid, 2.2

Emergency Response Guide Number 120

<u>TDG</u>

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class 2.2

Description UN1977, Nitrogen, refrigerated liquid, 2.2

MEX

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class 2.2

Description UN1977, Nitrogen, refrigerated liquid, 2.2

IATA

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class 2.2 ERG Code 2L Special Provisions A152

Description UN1977, Nitrogen, refrigerated liquid, 2.2

<u>IMDG</u>

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class2.2EmS-No.F-C, S-VSpecial Provisions345, 346

Description UN1977, Nitrogen, refrigerated liquid, 2.2

ADR

UN/ID no. UN1977

Proper shipping name Nitrogen, refrigerated liquid

Hazard Class 2.2

Classification code 3A
Tunnel restriction code (C/E)

Special Provisions 345, 346, 593

Description UN1977, Nitrogen, refrigerated liquid, 2.2, (C/E)

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Complies
EINECS/ELINCS Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

16. OTHER INFORMATION

NFPA Health hazards 3 Flammability 0 Instability 0 Physical and Chemical

Properties Simple asphyxiant

Note: Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2009, CGA Recommended Hazard Ratings for Compressed Gases, 3rd Edition.

Issue Date17-Feb-2015Revision Date17-Feb-2015Revision NoteInitial Release.

General Disclaimer

For terms and conditions, including limitation of liability, please refer to the purchase agreement in effect between Linde Gas Singapore and the purchaser.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

End of Safety Data Sheet